


KK 1500		ÜTB no: T1501	
Dimensions	Shape:	Rectangular	
	Volume under lid:	1,5 ltr +/- 50 ml	No space left
	Tam dolu Hacim:	1,60 ltr +/- 50 ml	No space left
	Top dia (Ext) without lid	231 mm X 170 mm	Height without lid 62 mm +/- 1 mm
	Top dia (Ext) with lid	231 mm X 170 mm	Height with lid 63 mm +/- 1 mm
	Base diameter (Ext):	215 mm X 154 mm	
Lid system	Safety system	Tamper evidence lock	
	Safety circle	Yes	
	Tamper proof	Differs with lid type	
	Lid Types	Standard	
Handle	Handles	Plastic standard	
Printing	Decoration options:	xxx Offset lid print	
	Offset Decoration Area:	xxx	
	Printing gap	xxx	
	Printing overlap	xxx	
Plastic Material	Material options:	PP Copolymer,	
	Masterbatch options:	General Colours: White 101, Transparent, Naturel, Other colours can be asked	
	Approved:	All plastic polymers, masterbatches and atistatic agents are approved by Turkish Ministry of Agr. and Rural Affairs.	
			
Sturdiness	<u>Sturdiness</u>	9 kg (=the max weight that the pail which is at the base of stack can carry Stacking test made on 23° C for 2 months with standart PP raw material. Stackability may vary with diffrent factors. Data above are for indication. For that reasons, customers should make their own tests to determine stacking and transportation quantities. For transparent materials the durability is lower, customers must consider that before stacking transparent products.	
Weight	Pail weight (nude):	81 g +/- 2 g	
	Lid weight:	48 g +/- 3 g	
	Weight plastic handle:	xxx	
Packing	Palette 1300x1100:	3.000 pieces	Lid carton box: YES
	No of sticks on palette	xx pieces.	Carton box size: xxxXxxxXxxx
	Pieces per stick	75 pieces	Lids in a carton box: 600 pieces
			Carton boxes in a palette: xx pieces
Performance	Hot filling:	The standart material has a very good heat resistance and the pail is suitable for hot filling. But, plastic pail become flexible when hot filled on high temperatures and customers must carrefully stack after hot filling. After cooling of the product and pail, the pail regains its original stacking strength.	
	Cold reactions:	The standard PP material for white/coloured products resists temperatures up to -20° C. Deep freezing under -20° C require a special PP .Standard transparent products may become fragile at temperatures below 0° C and special transparent resins are available on request for applications below freezing.	
	Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 10 months after the date of the delivery, under to suitable storage.	
	Quality info:	Deviations in the product specifications in this data sheet can be 0.1% or less (i.e. 10 items per 1,000) on a 12 months basis are considered acceptable and therefore cannot be considered as a defect.	
Other:	UN approval:	NO	
	Notes:		